



## Bentomat® & Claymax® Panel & Roll Specifications

### Panel Specifications

PRODUCTS	DIMENSIONS Width x Length	AREA	EFFECTIVE AREA
BENTOMAT® ST	15 ft x 150 ft (4.6 m x 45.7 m)	2,250 ft <sup>2</sup> (209 m <sup>2</sup> )	2,145 ft <sup>2</sup> (200 m <sup>2</sup> )
BENTOMAT SDN	14.5 ft x 150 ft (4.4 m x 45.7 m)	2,175 ft <sup>2</sup> (202 m <sup>2</sup> )	2,071 ft <sup>2</sup> (193 m <sup>2</sup> )
BENTOMAT DN	14.5 ft x 150 ft (4.4 m x 45.7 m)	2,175 ft <sup>2</sup> (202 m <sup>2</sup> )	2,071 ft <sup>2</sup> (193 m <sup>2</sup> )
BENTOMAT YSDN	14.5 ft x 200 ft (4.4 m x 60.9 m)	2,900 ft <sup>2</sup> (270 m <sup>2</sup> )	2,771 ft <sup>2</sup> (258 m <sup>2</sup> )
BENTOMAT CL Lovell, WY Plant	15 ft x 150 ft (4.6 m x 45.7 m)	2,250 ft <sup>2</sup> (209 m <sup>2</sup> )	2,145 ft <sup>2</sup> (200 m <sup>2</sup> )
BENTOMAT CL Fairmount, GA Plant	14.5 ft x 150 ft (4.4 m x 45.7 m)	2,175 ft <sup>2</sup> (202 m <sup>2</sup> )	2,071 ft <sup>2</sup> (193 m <sup>2</sup> )
BENTOMAT CLT	15 ft x 150 ft (4.6 m x 45.7 m)	2,250 ft <sup>2</sup> (209 m <sup>2</sup> )	2,145 ft <sup>2</sup> (200 m <sup>2</sup> )
CLAYMAX® 200R	15 ft x 150 ft (4.6 m x 45.7 m)	2,250 ft <sup>2</sup> (209 m <sup>2</sup> )	2,145 ft <sup>2</sup> (200 m <sup>2</sup> )
CLAYMAX 600CL Lovell, WY Plant	15 ft x 150 ft (4.6 m x 45.7 m)	2,250 ft <sup>2</sup> (209 m <sup>2</sup> )	2,145 ft <sup>2</sup> (200 m <sup>2</sup> )
CLAYMAX 600CL Fairmount, GA Plant	14.5 ft x 150 ft (4.4 m x 45.7 m)	2,175 ft <sup>2</sup> (202 m <sup>2</sup> )	2,071 ft <sup>2</sup> (193 m <sup>2</sup> )

### Roll Specifications

PRODUCTS	DIMENSIONS Length x Diameter (Avg.)	NOMINAL WEIGHT	ROLLS / TRUCKLOAD
BENTOMAT ST	16 ft x 24 in (4.9 m x 610 mm)	2,600 lbs (1180 kg)	16 rolls per truckload
BENTOMAT SDN	16 ft x 24 in (4.9 m x 610 mm)	2,650 lbs (1200 kg)	15 rolls per truckload
BENTOMAT DN	16 ft x 24 in (4.9 m x 610 mm)	2,650 lbs (1200 kg)	15 rolls per truckload
BENTOMAT YSDN	15 ft x 24 in (4.6 m x 600 mm)	2,500 lbs (1133 kg)	17 rolls per truckload
BENTOMAT CL	16 ft x 24 in (4.9 m x 610 mm)	2,650 lbs (1200 kg)	15 rolls per truckload
BENTOMAT CLT	16 ft x 26 in (4.9 m x 660 mm)	2,950 lbs (1340 kg)	15 rolls per truckload
CLAYMAX 200R	16 ft x 20 in (4.9 m x 510 mm)	2,750 lbs (1250 kg)	15 rolls per truckload
CLAYMAX 600CL	16 ft x 20 in (4.9 m x 510 mm)	2,825 lbs (1250 kg)	15 rolls per truckload

#### Unloading and handling equipment for all GCL products:

- Spreader bar and core pipe: Spreader bar 17 ft (5.2 m) long; core pipe 20 ft (6.1 m) long, nominal pipe size, XXH.
- Core Pipe for Bentomat YSDN: 16 ft (4.9 m); O.D. = 3.5 in (90 mm)
- A solid 3.5 in. (90 mm) O.D. x 14.5 ft (4.4 m) solid steel pipe stinger attachment for a forklift.
- Slings: 2 Polyester slings are required, approximately 12 ft (3.7 m) long x 2 in (50 mm) wide each.
- Vehicle needed: Front end loader or forklift (are typical).

#### Standard Roll Specifications:

- Packaging: U.V. resistant polyethylene sleeve.



1500 West Shure Drive, 5<sup>th</sup> Floor, Arlington Heights, IL 60004 USA 800.527.9948 Fax 847.577.5566

For the most up-to-date product information please visit our website, [www.cetco.com](http://www.cetco.com)

A wholly owned subsidiary of AMCOL International Corporation

The information and data contained herein are believed to be accurate and reliable, CETCO makes no warranty of any kind and accepts no responsibility for the results obtained through application of this information.