

## LANDLOK® TRM 435

**LANDLOK® TRM 435** is manufactured at an SI Geosolutions' facility having achieved ISO-9002 certification for its systematic approach to quality. **LANDLOK® TRM 435** turf reinforcement mat (TRM) **features X3™ technology** that consists of a dense web of crimped, interlocking, multi-lobed polypropylene fibers positioned between two biaxially oriented nets and mechanically bound together by parallel stitching with polypropylene thread. The TRM is designed to accelerate seedling emergence, exhibit high resiliency, and possess strength and elongation properties to limit stretching in a saturated condition. Every component of the TRM is stabilized against chemical and ultraviolet degradation which are normally found in a natural soil environment. Furthermore, the TRM contains no biodegradable components. **LANDLOK® TRM 435** conforms to the property values listed below<sup>1</sup> that have been derived from manufacturing quality control and independent testing performed by SI Geosolutions' GAI-LAP accredited and third-party laboratories:

**MARV<sup>2</sup>**

PROPERTY	TEST METHOD	ENGLISH	METRIC
<b>Physical</b>			
Mass/Unit Area	ASTM D6566	8.0 oz/yd <sup>2</sup>	271 g/m <sup>2</sup>
Thickness	ASTM D6525	0.35 in	8.9 mm
Light Penetration (% Passing)	ASTM D6567	40%	40%
Color	Visual	Green	
<b>Mechanical</b>			
Tensile Strength	ASTM D6818	225 x 175 lb/ft	3.3 x 2.6 kN/m
Tensile Elongation	ASTM D6818	50% (max)	50% (max)
Resiliency	ASTM D6524	80%	80%
Flexibility	ASTM D6575	0.015 in-lb (avg)	16,000 mg-cm (avg)
<b>Durability</b>			
UV Resistance @ 1000 hrs	ASTM D4355	80%	80%
<b>Performance</b>			
Shear Stress <sup>3</sup>	Large Scale	5 lb/ft <sup>2</sup>	240 Pa
Manning's "n" <sup>4</sup>	Calculated	0.025	0.025
Seedling Emergence <sup>5</sup>	ECTC Draft Method #4	—	—
<b>Roll Size</b>		6.5 ft x 138.5 ft	2.0 m x 42.2 m

**NOTES**

- The property values listed are effective 3/01/2004 and are subject to change without notice.
- MARV indicates minimum average roll value calculated as the typical minus two standard deviations. Statistically, it yields a 97.7% degree of confidence that any sample taken during quality assurance testing will exceed the value reported.
- Maximum permissible shear stress has been obtained through vegetated testing programs featuring specific soil types, vegetation classes, flow conditions, and failure criteria. These conditions may not be relevant to every project nor are they replicated by other manufacturers. Please contact SI Geosolutions for further information.
- Calculated as typical values from large-scale flexible channel lining test programs with a flow depth of 6 to 12 inches.
- Calculated as average plant height obtained with tall fescue grass seed in sand 14 days after seeding.

SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT FURNISHED HEREUNDER OTHER THAN AT THE TIME OF DELIVERY IT SHALL BE OF THE QUALITY AND SPECIFICATION STATED HEREIN. ANY IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS EXPRESSLY EXCLUDED, AND, TO THE EXTENT THAT IT IS CONTRARY TO THE FOREGOING SENTENCE, ANY IMPLIED WARRANTY OF MERCHANTABILITY IS EXPRESSLY EXCLUDED. ANY RECOMMENDATIONS MADE BY SELLER CONCERNING THE USES OR APPLICATIONS OF SAID PRODUCT ARE BELIEVED RELIABLE AND SELLER MAKES NO WARRANTY OF RESULTS TO BE OBTAINED. IF THE PRODUCT DOES NOT MEET SI GEOSOLUTIONS' CURRENT PUBLISHED SPECIFICATIONS, AND THE CUSTOMER GIVES NOTICE TO SI GEOSOLUTIONS BEFORE INSTALLING THE PRODUCT, THEN SI GEOSOLUTIONS WILL REPLACE THE PRODUCT WITHOUT CHARGE OR REFUND THE PURCHASE PRICE.