



CELLULOSE FIBER

with TACKING AGENT 3^o

*PERFORMANCE PRODUCTS FOR
HYDRO-SEEDING PROFESSIONALS*

- MEETS OR EXCEEDS ALL REQUIREMENTS FOR WOOD CELLULOSE FIBER MULCH
- UNIVERSITY TESTED TO CONTROL EROSION WITHOUT HAVING TO CURE
- REDUCES FRICTION IN HOSE AND INCREASES SLURRY SHOOTING DISTANCE
- HOLDS MORE WATER – IMPROVING TURF ESTABLISHMENT

DIRECTIONS FOR USE

WHILE FILLING HYDRAULIC SEEDER WITH WATER ADD SEED, CELLULOSE FIBER WITH TACKING AGENT 3 AND FERTILIZER. PLEASE REFER TO EQUIPMENT MANUFACTURER'S LOADING INSTRUCTIONS.



PHYSICAL PROPERTIES

MOISTURE CONTENT	12% +-3
ORGANIC CONTENT	90.0% +-3
pH RANGE	7.0 +-2
TACKING AGENT III	3.0% MIN
WATER HOLDING CAPACITY	1200% MIN

TYPICAL APPLICATION RATE

3 TO 1 SLOPE	2000 LBS / ACRE
STRAW MULCH BINDING	500 LBS / ACRE

PACKAGING

NET WEIGHT 50 LB BALE, SHIPPED 40 BALES
PER 42 x 48 PALLET WITH UV PALLET COVER



DISTRIBUTED BY