BLEND

with TACKING AGENT 3Ô

PERFORMANCE PRODUCTS FOR HYDRO-SEEDING PROFESSIONALS

- MEETS OR EXCEEDS ALL REQUIREMENTS FOR WOOD AND PAPER FIBER MULCH
- UNIVERSITY TESTED TO CONTROL EROSION WITHOUT HAVING TO CURE
- HOLDS MORE WATER, REDUCES FRICTION IN HOSE AND INCREASES SLURRY SHOOTING DISTANCE

DIRECTIONS FOR USE

WHILE FILLING HYDRAULIC SEEDER WITH WATER ADD SEED, 70 / 30 BLEND WITH TACKING AGENT 3 MULCH AND FERTILIZER. PLEASE REFER TO EQUIPMENT MANUFACTURER'S LOADING INSTRUCTIONS.

PHYSICAL PROPERTIES

MOISTURE CONTENT	12% +-3
ORGANIC CONTENT	99.0% +-1
WOOD FIBER	70% MIN
PAPER FIBER	30% MAX
ASH CONTENT	1.0% +-1
pH RANGE	4.8 +-2
TACKING AGENT 3	3.0% MIN
WATER HOLDING CAPACITY	1200% MIN

TYPICAL APPLICATION RATE

3 TO 1 SLOPE	2000 LBS / ACRE

PACKAGING

NET WEIGHT 50 LB BALE, SHIPPED 40 BALES PER 42 x 48 PALLET WITH UV PALLET COVER

DISTRIBUTED BY

PROFILE Products LLC – 750 LAKE COOK ROAD – SUITE 440 – BUFFALO GROVE, IL 60089
800-726-6371 - Fax 847-215-0577 – 847-215-1144 www.terra-mulch.com