TERRA WOOD™

with TACKING AGENT 3

(FORMERLY LABELED AS WOOD FIBER)

PERFORMANCE PRODUCTS FOR HYDRO-SEEDING PROFESSIONALS

- MEETS OR EXCEEDS ALL REQUIREMENTS FOR WOOD FIBER MULCH
- REDUCES FRICTION IN HOSE, INCREASES SLURRY SHOOTING DISTANCE AND UNIVERSITY TESTED TO CONTROL EROSION WITHOUT HAVING TO CURE
- DYED A DARK GREEN COLOR FOR EASY METERING

DIRECTIONS FOR USE

WHILE FILLING HYDRAULIC SEEDER 1/3 FULL WITH WATER ADD SEED, WOOD FIBER w/TACKING AGENT 3 MULCH AND FERTILIZER TO TANK. PLEASE REFER TO EQUIPMENT MANUFACTURER'S LOADING INSTRUCTIONS.

PHYSICAL PROPERTIES

MOISTURE CONTENT	12% +-3
ORGANIC CONTENT	96.2% +-.4
ASH CONTENT	.8% +-.4
TACKIFIER	3.0% MIN
pH RANGE	4.8 +-2
WATER HOLDING CAPACITY	1350% MIN

TYPICAL APPLICATION RATE

2.5 TO 1 SLOPE	2000 LBS / AC

PACKAGING

NET WEIGHT 50 LB BALE, 40 BALES PER 42 x 48 SKID WITH A UV TREATED PALLET COVER

DISTRIBUTED BY

PROFILE Products LLC – 750 LAKE COOK ROAD – SUITE 440 – BUFFALO GROVE, IL 60089
800-726-6371 - Fax 847-215-0577 – 847-215-1144 www.terra-mulch.com