

Distributed by:



# KINTEX

Industries, LLC

102 Brownfield Drive  
Summerville, South Carolina, 29483

## Product Specifications

# WevTex 403

**WevTex 403** is a woven polypropylene monofilament textile. It is inert to biological degradation and resistant to naturally encountered chemicals, alkalis and acids.

<u>Property</u>	<u>Test Method</u>	<u>Value</u>
Grab Tensile Strength (lbs) (Warp/Fill)	ASTM D 4632	325/200
Trapezoid Tear Strength (lbs) (Warp/Fill)	ASTM D 4533	90/50
Puncture (lbs)	ASTM D 4833	115
Burst (psi)	ASTM D 751	460
Vertical Water Flow Rate (gal/min/sf)	ASTM D 4491	145
UV Resistance (% strength retained)	ASTM D 4355	70
AOS (mm/sieve#)	ASTM D 4751	.60/30

## Roll Size

Width (inches)	144
Length (feet)	300
Area (square yards)	400
Weight (pounds)	150

Telephone: 843-832-6860,  
Email: [kintex@knology.net](mailto:kintex@knology.net),

Fax: 843-832-5953,  
Cell: 843-343-3401,

Toll Free: 800-626-0454  
Website: [www.kintex.net](http://www.kintex.net)